

MATERIAL SAFETY DATA SHEET

FLAME CONTROL NO. 77 CABLE MASTIC

Page 1 of 4

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

FLAME CONTROL COATINGS LLC
4120 HYDE PARK BLVD.
NIAGARA FALLS, N.Y. 14305

TRADE NAME: NO. 77CABLE MASTIC
COLOR: WHITE AND PASTEL TINTS
MAIN USE: FIRE RETARDANT MASTIC

EMERGENCY TELEPHONE NUMBER: 800-535-5053

INITIAL ISSUE DATE: NOVEMBER 12, 2011

REVISION DATE:

PREPARED BY: J.W. ESSIG

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS	Wt. %	CAS Number
ALUMINUM TRIHYDRATE	10-30	021645-51-2
CALCIUM CARBONATE	10-30	001317-65-3
PROPYLENE GLYCOL	1-5	000057-55-6
TITANIUM DIOXIDE	1-5	013463-67-7
FIBROUS GLASS	5-10	065997-17-3
ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE	0.1-1.0	000112-07-2
ETHYLENE GLYCOL	1-5	000107-21-1

SECTION 3: HAZARDS IDENTIFICATION

PRIMARY ROUTES OF ENTRY: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

HEALTH HAZARDS (ACUTE AND CHRONIC EXPOSURES)

EYES:

ACUTE – MAY CAUSE MILD IRRITATION WITH BLURRED VISION.

CHRONIC– ND

SKIN CONTACT:

ACUTE – TRANSIENT IRRITATION AND REDNESS.

CHRONIC – ND

SKIN ABSORPTION:

ACUTE – ND

CHRONIC – ND

INHALATION:

ACUTE – INHALATION OF MISTS MAY CAUSE MILD RESPIRATORY TRACT IRRITATION.

CHRONIC – EXCESSIVE EXPOSURE TO HEATED VAPORS CAN CAUSE IRRITATION OF EYES, NOSE AND THROAT.

INGESTION:

ACUTE – MAY CAUSE MILD IRRITATION OF GASTRO-INTESTINAL TRACT

CHRONIC – ND

CONDITIONS AGGRAVATED BY EXPOSURE: NONE KNOWN

OVEREXPOSURE EFFECTS: IRRITATION

IRRITANCY: YES - REVERSIBLE

SENSITIZER: NO

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE AFFECTED PERSON FROM AREA. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. IF BREATHING REMAINS OR BECOMES LABORED, SEEK MEDICAL ATTENTION.

INGESTION: GIVE 3 – 4 GLASSES OF MILK OR WATER. **DO NOT INDUCE VOMITING.** SEEK MEDICAL ATTENTION.

MATERIAL SAFETY DATA SHEET

FLAME CONTROL NO. 77 CABLE MASTIC

Page 2 of 4

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: NA

CONDITIONS OF FLAMMABILITY: NA

FLAMMABLE LIMITS: LEL: NE UEL: NE

OSHA CLASS: NONE SHOWN

AUTO IGNITION TEMP.: NA

HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂

SENSITIVITY TO IMPACT: NONE

SENSITIVITY TO STATIC DISCHARGE: NONE

EXTINGUISHING MEDIA: WATER, CO₂, DRY CHEMICAL

SPECIAL FIRE FIGHTING PROCEDURES: NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.

UNUSUAL FIRE AND EXPLOSIVE HAZARDS: POLYMER FILM CAN BURN, MATERIAL CAN SPLATTER ABOVE 100°C

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

GENERAL: STORE IN COOL, WELL VENTILATED AREAS. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID PROLONGED INHALATION OF HEATED VAPORS OR MISTS. AVOID PROLONGED SKIN CONTACT.

STORAGE: STORE BETWEEN 40°F AND 100°F PROTECTED FROM FROST AND DIRECT SUNLIGHT.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

INGREDIENTS (CAS)	<u>EXPOSURE LIMITS (ppm)</u>				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	TLV	
021645-51-2	10mg/m ³	ND	10mg/m ³	ND	(SEE NOTE 1)
001317-65-3	15mg/m ³	ND	15mg/m ³	ND	(SEE NOTE 1)
000057-55-6	NE	NE	NE	NE	
013463-67-7	10mg/m ³	ND	10mg/m ³	ND	(SEE NOTE 1)
065997-17-3	5mg/m ³	ND	5mg/m ³	ND	(SEE NOTE 1)
000112-07-2	20	NE	20	NE	
000107-21-1	NE	125 mg/m ³	NE	100 mg/m ³	

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK
NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

MATERIAL SAFETY DATA SHEET

FLAME CONTROL NO. 77 CABLE MASTIC

Page 3 of 4

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >100°C (>212°F)

SPECIFIC GRAVITY: 1.45-1.55

VAPOR PRESSURE: ND

MELTING POINT: ND

VAPOR DENSITY: >1
(AIR = 1)

EVAPORATION RATE: <1
(BUTYL ACETATE = 1)

SOLUBILITY IN WATER: DILUTABLE

pH: 8.0 TO 11.5

COEFFICIENT of WATER/OIL DISTRIBUTION: ND

ODOR THRESHOLD: ND

APPEARANCE AND ODOR: WHITE OR PASTEL PIGMENTED LIQUID, MILD ODOR

% VOLATILES BY VOLUME: 48%

% SOLIDS BY WEIGHT: 68%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID: AVOID ELEVATED TEMPERATURES

INCOMPATIBILITY (MATERIAL TO AVOID): NONE KNOWN

HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR

CONDITIONS TO AVOID: KEEP FROM FREEZING

SECTION 11: TOXICOLOGICAL INFORMATION

CARCINOGENIC DATA: NTP: NONE

OSHA: NONE

IARC: NONE

TERATOGENICITY: NO

MUTAGENICITY: NO

EMBRYOTOXICITY: NO

SYNERGISTIC MATERIAL: NO

ACUTE TOXICITY EFFECTS: NA

LONG TERM EXPERIENCE OF THIS PRODUCT TYPE INDICATES NO DANGER TO HEALTH WHEN PROPERLY HANDLED UNDER INDUSTRIAL CONDITIONS.

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: NE

ECOTOXICITY: NE

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: AT THIS TIME, MATERIAL AND ITS CONTAINERS WOULD NOT BE CONSIDERED HAZARDOUS WASTE AS DEFINED UNDER RCRA REGULATIONS. CHECK FOR DISPOSAL COMPLIANCE UNDER FEDERAL, STATE AND LOCAL AUTHORITIES.

SECTION 14: TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: LIQUID LATEX, NOT REGULATED BY DOT

HAZARD CLASS: NONE

PACKING GROUP: NOT APPLICABLE

UN NUMBER: NOT APPLICABLE

IMO SHIPPING DATA: NOT REGULATED

ICAO/IATA SHIPPING DATA: NOT REGULATED

SECTION 15: REGULATORY INFORMATION

MATERIAL VOC = 75 gram / liter

COATING VOC = 126 gram/liter

TSCA (TOXIC SUBSTANCE CONTROL ACT): ALL COMPONENTS ARE LISTED IN THE TSCA CHEMICAL SUBSTANCE INVENTORY.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION and LIABILITY ACT): ND

MATERIAL SAFETY DATA SHEET

FLAME CONTROL NO. 77 CABLE MASTIC

Page 4 of 4

SECTION 15: REGULATORY INFORMATION (CON'T)

SARA TITLE III

SECTION 312 HAZARD CLASS: SLIGHT HEALTH HAZARD

SECTION 313 LISTED INGREDIENTS: ETHYLENE GLYCOL (CAS #00107-21-1), ETHYLENE GLYCOL MONOBUTYL ETHER ACETATE (CAS #000112-07-2)

CALIFORNIA PROPOSITION 65: The below list of compounds is known to the State of California to cause cancer, birth defects or other reproductive harm: ALUMINUM TRIHYDRATE

SECTION 16: OTHER INFORMATION

HAZARD RATING

HMIS: HEALTH 1 FLAMMABILITY 1 REACTIVITY 0

LEGEND

ACGIH: AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGEIENISTS
OSHA: OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION
STEL: SHORT TERM EXPOSURE LIMIT
TWA: TIME WEIGHTED AVERAGE
PEL: PERMISSABLE EXPOSURE LIMIT
TLV: THRESHOLD LIMIT VALUE
NA: NOT APPLICABLE
NE: NOT ESTABLISHED
ND: NO DATA

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the accuracy of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.